



DBL1400 / DBL1425

DOLPHIN PANEL MOUNTED INFRARED TAP – LONGER VERSION

- › WRAS approved product
- › Touch Free Tap – for ultimate hygiene – prevents cross contamination
- › Quality polished or brushed chrome plated brass finishes available from stock – other finishes available to special order
- › Water Supply: Single inlet – cold or pre-mixed
- › Flexible pipe – 50cm
- › Cable length – 25cm coming out bottom on the tap; transformer comes with a 5m length lead on it
- › Flow rate – 3.5 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates such as 1.89 and 1.33 LPM available to special order – please enquire)
- › Flow time once user's hands are removed from the tap – 1 second (adjustable by using remote control **DB51**)
- › Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits
- › A TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- › Interchangeable TT M16/18 Neoperl Aerator insert
- › Power Source: Plug-in 9 Volt transformers or 9 Volt Battery (with low battery warning) – Auto adjusting sensor range 50-170 mm
- › Sensor range and tap settings including optional hygiene flush and security time can be adjusted by using remote control (**DB51**)
- › Mandatory Hygiene Flush feature can be specified to combat Legionella
- › 2 year manufacturer's warranty
- › Maximum water temperature 70°C
- › Operating pressure 0.5–8.0 bar (7–116 PSI)
- › Projection to outlet- 238mm / Projection to end - 275mm
- › For shorter version please see our **DB1400** / **DB51425**

DIAMETER	28 MM
PROJECTION	275 MM

PRODUCT CODES

- › Panel Mounted Infrared Tap Battery Operated In Satin Finish **DBL1400S-2**
- › Panel Mounted Infrared Tap Battery Operated In Mirror Polish Finish **DBL1400C**
- › Panel Mounted Infrared Tap Transformer Operated In Satin Finish **DBL1425S-2**
- › Panel Mounted Infrared Tap Transformer Operated In Mirror Polish Finish **DBL14025C**

