


02.4011



02.4411

02.4011

DOLPHIN RECESSED HIGH SPEED HAND DRYER

- > 1kW recessed high speed hand dryer
- > Available to match any international spectrum colour or your own colour specification
- > Alternative finishes: satin stainless steel, coloured acrylic, coloured glass or coloured corian
- > Door Fascia: 4-5mm acrylic to ISO 7823-1 (Acrylic thickness may vary depending on acrylic manufacturer. Contact Dolphin Solutions Ltd with your colour specification) and stainless steel backed.
- > Bowl: 0.7mm satin finish stainless steel grade 1.4301 (304) to BS EN 10088-1
- > Back box: 0.9mm stainless steel grade 1.4301 (304) to BS EN 10088-1
- > IP23 rated
- > Operating Voltage 240VAC 50/60Hz 1kW
- > Output Warm Air Volume 42-60 CFM (71-102 m³/h)
- > Adjustable Output Warm Air Temperature 131°F (55°C) at ambient T = 77°F (25°C),
- > Adjustable Output Air Speed 102mph (150ft/s) [45.5m/s {164km/h}] – 157mph (230ft/s) [70m/s {252km/h}] Adjustable
- > Sound Level 68.9 dB-A Min @ 2m, 74.3 dB-A Max @ 2m, Adjustable
- > Motor Type 0.67HP, 16-29krpm Brush Type, Dual Ball Bearings, Adjustable
- > Motor Thermal Protection 240VAC, Auto Resetting Thermostat turns unit off @ 203°F (95°C)
- > Heater Element ON/OFF Heating options: Range Adjustable, 325-500W Heater
- > Thermal Protection Auto Resetting Thermostat turns heater element off @ 185°F (85°C), Resets @ 167°F (75°C), Thermal cut-off @ 288°F (142°C)
- > Drying Time Less than 15 seconds
- > Standby Power Less than 0.5W
- > Circuit Operation Infrared Automatic, self-adjusting
- > Sensor Range Standard 152mm ±20mm (6")
- > Timing Protection 60 seconds auto shut off
- > Timing Duration 1 second delayed turn off after last sensor reading
- > Cover Type 1.2mm 1.4301(304) stainless steel
- > Net Weight 8.5Kg
- > Data varies depending on motor speed and heater element on/off

WIDTH	373MM
HEIGHT	447.5MM
PROJECTION	6MM

PRODUCT CODES

- 02.4011 - With stainless steel front
- 02.4011.1 - With glass front
- 02.4011.2 - With acrylic front
- 02.4011.3 - With corian front
- 02.4411.1/2/3 - Surface mounted version