



DB5580.E

DOLPHIN ELECTRONIC INFRARED FLUSH PLATE

- › Compatible with our DB5510.E and DB5511.E cisterns
- › Available to be powder coated in any RAL colour, and ceramic coated in a wide range of colours
- › Require Electronic version Dolphin cistern which comes with compatible motor already installed (currently not available on the short version 820mm cistern)
- › Designed to be hardwired into 240v circuit - no battery option available
- › Red LED feedback
- › Optional bluetooth connection to Dolphin App or gateway device (to take you to Dolphin cloud or BMS) to provide setting possibilities, diagnosis and usage statistics such as Total no. of uses, Number and type of flushes, Water consumption (estimated by flush volumes), Operating hours since first used, Average uses, Time since last usage or hygiene flush
- › Automatic dual flush - Option of manual only (users hand within close proximity – 1 second hold is short flush, 3 second hold is long flush), or manual and automatic (determines short or long flush based on length and proximity of the user in the sensor field) activation which can be changed manually at the sensor window, via the Dolphin app or preset by Dolphin according to specification
- › Optional radio version that enable connection of a radio receiver providing the option to flush the WC remotely from a radio transmitter affixed to the drop down rail
- › Cleaning mode settings (flush won't operate) and Hygiene flush settings
- › Adjustable sensor range

WIDTH	215MM
HEIGHT	145MM
PROJECTION	2MM

PRODUCT CODES

- DB5580.E** - Automatic Infrared flush sensor
- DB5570.E** - Mini automatic Infrared flush sensor
- Compatible cisterns
- DB5510.E** - Electronic frameless cistern
- DB5511.E** - Electronic cistern & frame