



Certificate number: 2107718

Date issued 15th July 2021

Date expired 14th July 2026 Original/Amendment Original

Kiwa UK Regulation 4 (KUKreg4) Approval

ATS3 – Without Production Surveillance

Issued by Kiwa Watertec (UK)

Evaluation Guideline: Kiwa UK – EG004
Reference Standards: Regulators Specification
Model Designations: see Appendix

Manufacturer: Dolphin Solutions Limited.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied on to comply with the above Evaluation Guideline and Standards, and can be marked with the KUKreg4mark.

The intended use of this certificate is for compliance with Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales; 2009 Northern Ireland and 2014 Byelaws Scotland

This certificate has been issued in accordance with the Kiwa regulations for product certification

Signed on behalf of Kiwa Watertec

David Jay,
Business Unit Manager – Authorised Signatory
Kiwa Watertec

CERTIFICATE

390177301

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate issued to:
Dolphin Solutions Limited
Southpoint, Compass Park
Bodiam
East Sussex
TN32 5BS



UK Approval Certificate (page 2 of 2)

Appendix to Certificate 2107718

The following products are covered by this certificate -

<p>PRODUCT DESCRIPTION Range of single hole, single outlet (fixed) combination tap assemblies with brass bodies (in various finishes). Incorporating an infrared sensor which operates a solenoid valve to control the flow. The spout outlet incorporates a plastic aerator. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S) DSaaa.bbb.ccc.d.ee – DS220 Series InForm SMART taps.</p> <p>Where 'aaa' denotes the mounting type, the following options are available: DS221 – straight spout; DS223 – bent spout.</p> <p>Where 'bbb' denotes the projection of the spout from body to spout outlet in mm. Range 95mm - 195mm in 25mm increments.</p> <p>Where 'ccc' denotes the height of the tap from the underside of the rosette to the top of the body in mm. Range 170mm – 370mm including 170mm, 260mm, 310mm & 370mm.</p> <p>Where 'd' denotes the material finish, the following options are available: .1 – brushed/satin, .2 - mirror polished, .3 - PVD on brushed/satin, .4 - PVD on mirror polished or .5 – powder coated (PC).</p> <p>Where 'ee' is a numerical code between .00-.99 which denotes the colour of the finished surface. This is only present and applicable on PVD (where 'd' is 3 or 4) or PC (where 'd' is 5) material finish options.</p> <p>Models may include an additional .R suffix which denotes that the tap is supplied without the rosette.</p>
<p>SIZE: ½" BSP (M).</p>
<p>SCOPE: Manufacturer recommended maximum working pressure 6 Bar & maximum operating temperature 60°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C. Deck Mounted.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES Consider balanced supplies or appropriate backflow protection at the inlets. If this tap or combination tap is installed so that its base is no lower than the spill over level of the receiving vessel a Type AUK3 air gap is achieved.</p>
<p>MARKING Dolphin logo on body.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes